


BZ 133A

Setting tool for blind rivets
Pneumatic-hydraulic | with permanent and intermittent extraction



The specialist for blind rivets up to 8.0 mm in diameter!

Special high-strength FERRO® BULB blind rivets (and similar types) are set easily and reliably by the combination of short stroke and **very high setting force (24,000 N!)**.

Our field service would be glad to present all our pneumatic-hydraulic tools to you.
Make an appointment!



Eminently suitable for FERRO® BULB blind rivets!



Nosepieces

321120000124	Nosepiece 4.0 mm
321120000125	Nosepiece 4.8/5.0 mm
321120000126	Nosepiece 6.0 mm
321120000127	Nosepiece 6.4 / 8.0 mm

Spare and wear parts

361122000022	Clamping sleeve
321120000010	Guide sleeve
361122000020	Clamping jaws
321120000014	O-ring clamping mechanism
311045000013	Pressure spring clamping mechanism

Family facts on the **HONSEL** pneumatic tools on page 65.

	2.4	3.0	3.2	4.0	4.8	5.0	6.0	6.4	8.0
					Aluminium				
					Steel				
					Stainless steel				
					Copper alloys				
	4.8 mm								
					24,000 N at 7 bar				
	2.34 kg								
					< 75 dB(A)				
									G 1/4 inside thread, can be fitted on left or right
	18 mm								
	3.5 litres								
<ul style="list-style-type: none"> • 1x BZ 133A pneumatic-hydraulic riveter in HONSEL L-Boxx® • 4x nosepiece • 1 set of clamping jaws • 1 bottle of hydraulic oil with refill unit • 2x mandrel collector 									
Item no. 320.133.000.000									

